

Small-sized Crawler Mucking Loader

LWLX-60D



LWLX-60D crawler mucking loader is a continuous excavating, drawing, loading and feeding equipment for material transportation. It is mainly been used in tunnel construction, diversion culvert, cave construction, etc.

LWLX-60D is suitable for tunnel section above 2.0×2.0, rock size ≤495 mm. The mucking loader shovel rocks thru dig arm, then load them to the conveyor trough, transport the rocks thru scraper to the rear, and off load rocks to MineTruck, dumper, shuttle car, or other transporting vehicles. The mucking loader may also be used to scale the forefield.

LWLX-60D uses diesel engine power for working and travelling;

The working mechanism include bucket, arm, boom, and rocker;

Crawling mechanism adopts hydraulic driving system, it is compact in structure, mobile for all terrain working conditions, and high grade-ability;


Pilot valve controlling, easy to operate, and to give maintenance.

FOPs+ROPs standard cabin, convenient for the driver to operate the mucking loader.

Your Ideal Mining Solutions for Underground Mining, Tunneling, Shaft sinking from China!

Main dimensions:		
Crawler ground contact length		2110 mm
Crawler inner width		700 mm
Track plate width:		300 mm
Transport trough inner width		495 mm
Dimensions during transport	Length	6650±50 mm
	Width	1600±50 mm
	Height	1900±50 mm
Dimensions during operation	Length	7850±50 mm
	Width	3100±50 mm
	Height	2350±50 mm

Working range	
Excavating width	≥ 3100 mm
Excavating distance (from feeder)	≥ 1450 mm
Excavating height	≥ 2350 mm
Excavating depth below ground level	≥ 500 mm
Dumping height	≥ 1350 mm
Minimum dumping height	1350 mm
Dumping distance	≥ 1600 mm
Maximum boom swinging angle	±55°
Adaptable tunnel size (Width×Height)	≥2m×2m




Functional Parameter	
Loading capacity	60m ³ /h
Engine power installed	44.7 kw/2800 rpm
Engine brand	CAT C2.2
Cooling method	Water-cooled
Diesel tank volume	95 L
Travel speed	0.25±0.05 m/s
Scraper chain	Single chain single motor
Speed of scraper chain	34 m/min
Grade ability	≤30°
Minimum turning radius	≥4 m
Ground contact pressure	≤0.1 MPa
Steering method	Hydraulic
Volume of Hydraulic tank	200 L
Rated working pressure	20 Mpa
Hydraulic pump	Plunger pump ×2 + gear pump ×2
Walking hydraulic motor	Radial plunger motor ×2
Transport hydraulic motor	Radial plunger motor ×1

✧ Diesel engine: CAT C2.2



✧ Options

- ✓ Engine compartment fire suppression system;
- ✓ Quick release device



- ✓ Lincoln Automatic lubrication system
- ✓ Doosan rock hammer



✧ Doosan Rock Hammer HB04S specifications

Model	HB04		
Net weight	silence type (h)	kg	155
	triangle (s)	kg	158
	erect (t)	kg	158
Hydraulic pressure	bar	88~117	
Hydraulic oil flow	liter/min	25~50	
Impact frequency	bpm	600~1,100	
Chisel diameter	m	53	
Suitable mucking loader weight	ton	2.5~4.5	

Your Ideal Mining Solutions for Underground Mining, Tunneling, Shaft sinking from China!

✧ AFTER-SALE SERVICE

Maximize productivity time and reduce costs for the clients.

- ✓ 1 year | 2000 engine hours warranty after commissioning;
- ✓ Rolling spare parts stock in the owner's country at supplier's cost;
- ✓ Free training in supplier's workshop;
- ✓ Free on-line training for the buyer's operators;
- ✓ 24-hours on-line support.

✧ Delivery reference:



Your Ideal Mining Solutions for Underground Mining, Tunneling, Shaft sinking from China!

